



## TECHNICAL DATA SHEET

PermaPro™		Limited 10 Year Warranty	
Test	Product Specifications	Test Method	
Composition	Woven Polypropylene		
Weight	1.9oz/yd <sup>2</sup> (+/-5%)	ASTM D 751	
Thickness	Avg. 5.0 mils		
Tensile Strength	MD 53 LB CD 44 LB	ASTM D 5034	
Tear Strength	MD 21 LB CD 19 LB	ASTM D 5587	
Water Resistance	PASS	ASTM D 779	
MTVR/Perms	12-15 Perms	ASTM E 96A	
UV Resistance	9 Months		
Fire Rating	Class A	ASTM E 84	
Roll Sizes	Width	Length (Rolls/Pallet)	
	3'	100'(150), 150'(135), 195'(120)	
	4.5'	100'(100), 150'(90), 195'(80)	
	9'	100'(78), 150'(55), 195'(45)	
	10'	100'(78), 150'(55), 195'(45)	

### PermaPro™

**FOR USE AS A REPLACEMENT FOR GRADE D PAPER AS A WATER RESISTIVE AND AIR INFILTRATION BARRIER**

Meets the following certifications: Complies with ICC-ES AC308 "Water-Resistive Barriers/Weather Barriers"

ICC report No. ESR-2514

**Disclaimer:** The information presented herein has been compiled from sources considered to be accurate and reliable but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Perma "R" Products' control are such that Perma "R" Products assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for specific purpose and to adopt such safety precautions as may be necessary.

2604 SUNSET DR. GRENADA, MS 38901

1-800-647-6130

WWW.PERMARPRODUCTS.COM

