



TECHNICAL DATA SHEET

PermaWrap™		Limited 10 Year Warranty	
TEST	PRODUCT SPECIFICATIONS		TEST METHOD
Composition	Woven Polypropylene		
Weight	2.2 oz/yd ² (+/-5%)		ASTM D 751
Thickness	Avg. 6.5 mils		
Tensile Strength	MD 80 LB	CD 40 LB	ASTM D 5034
Tear Strength	MD 40 LB	CD 13 LB	ASTM D 5587
Water Resistance	Pass		ASTM D 779
MTVR/Perms	12 - 15 Perms		ASTM E 96A
UV Resistance	9 Months		
Fire Rating	Class A		ASTM E 84
Roll Sizes Other Sizes Available	WIDTH		LENGTH (ROLLS/PALLET)
	3'		100'(150), 150'(135), 195'(120)
	4.5'		100'(100), 150'(90), 195'(80)
	9'		100'(78), 150'(55), 195'(45)
	10'		100'(78), 150'(55), 195'(45)

PermaWrap™

FOR USE AS A REPLACEMENT FOR GRADE D PAPER AS A WATER RESISTIVE AND AIR INFILTRATION BARRIER

Meets the following certifications: Complies with ICC AC308 "Water-Resistive Barriers/Weather Barriers"

ICC report No. ESR-2514

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Perma "R" Products' control are such that Perma "R" Products assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for specific purpose and to adopt such safety precautions as may be necessary.

2604 SUNSET DR. GRENADA, MS 38901

1-800-647-6130

WWW.PERMARPRODUCTS.COM

