



TECHNICAL DATA SHEET

STRAIGHT AND STRETCHABLE

Product Overview: ProTAK™ flashing is a butyl window and door flashing designed to bring you all the benefits of a non-asphalt tape. ProTAK's butyl adhesive contains zero asphalt, therefore will not have any of the inherent issues that asphalt and butyl/asphalt blend tapes have. ProTAK is changing the market and allowing you to obtain a superior performance butyl product.

Product Uses: Use ProTAK flashing for water penetration protection on all critical non-roof details such as parapets, recessed windows, pot shelves and sill pans. When integrated into the wall system and used properly, ProTAK Flashing will defend against water penetrating the building envelope, preventing costly mold and mildew growth.

Application Information: Ensure all involves surfaces are clean, dry and free of oil and moisture. Exercise care during application to prevent air, moisture, or contaminate entrapment. PermaTAK features a strong, flexible backing.

Packaging and Handling: Do not open until ready for use in order to maximize shelf life. Store at 60°F - 80°F. This Product is available in standard roll widths of 4", 6", 9", and 12". Standard roll length is 75 feet. Custom sizing is also available.

Raw Material Base.....Butyl
 Application Temperature.....20°F – 180°F
 Service Temperature.....20°F – 180°F
 Mold Growth (ASTM G-21).....No Growth
 Nail Sealability (AAMA 711-07).....Pass
 Nail Sealability (ASTM D-1970).....Pass
 90° Peel Plywood (AAMA 711-07).....2.31 psi
 90° Peel OSB (AAMA 711-07).....2.60 psi
 90° Peel Facer (AAMA 711-07).....2.49 psi

Solids by Weight.....100%
 UV Exposure.....Resistant up to 6 mos.
 Physical State.....Solid
 Odor.....Odorless
 Staining.....None
 USGBC.....Eligible for LEED compliance credits
 Adhesive Thickness.....Straight 14 - 16 mils
 Adhesive Thickness.....Stretchable 55 - 68 mils

Product	Size	Rolls Per Case	Cases Per Pallet	Rolls Per Pallet
PermaTAK and ProTAK Straight Flashing	4" x 75'	12	48	576
	6" x 75'	8	48	384
	9" x 75'	4	48	192
PermaTak and ProTAK Stretchable Flashing	6" x 75'	1	48	48
	9" x 75'	1	48	48

Non standard sizes available by special order

Disclaimer: The information presented herein has been compiled from sources considered to be accurate and reliable but is not guaranteed to be so. In practice, the differences in materials, substrates, storage conditions, actual site conditions and other factors outside of Perma "R" Products' control are such that Perma "R" Products assumes no liability, nor makes any warranty, express or implied for such information, recommendations or instructions related to its products. It is the users responsibility to determine the suitability of any material for specific purpose and to adopt such safety precautions as may be necessary.

2604 SUNSET DR. GRENADA, MS 38901
 1-800-647-6130
 WWW.PERMARPRODUCTS.COM

