

ROOFING SOLUTIONS

UNDERLAYMENT COLLECTION



OUR PRODUCTS

HIGH QUALITY PERFORMANCE COMES FROM A HIGH-QUALITY PRODUCT

At Perma “R” Products, our goal is to provide “best in class” products. We stand apart from other roof underlayment manufacturers with our quality roof underlayment’s and exceptional service.

KNOW WHAT’S UNDER YOUR ROOF

With our selection of synthetic underlayments, we have the right product for the right roof covering. Our underlayments are designed to replace, and outperform traditional asphalt felts. Whether you choose ProFeltPlus™ for under asphalt shingles or PermaFeltGold™ for under slate roofing, you can rest easy knowing you have the right product for the job no matter what final roof covering is used.

Each of our felts are a bit different, but no matter which one you choose, know you’re getting a high-quality product that will not rot, dry out, nor support mold growth. These are all key factors that go into putting a roof on. Unlike traditional asphalt felts, Perma “R” Products underlayments will not break down when exposed to UV rays. As a bonus, all of our roofing underlayments are 100% recyclable.

Perma “R” Products roofing felts offer rugged strength and durability on the job site meaning you can say good bye to blow offs and tears. After being installed, walking around on your roofing project should not be a hazard to your health. Our premium series felts have a proprietary embossed slip-resistant coating and our pro series felts have a non-woven fabric laminated to the top side to aid in better traction.*

Choose quality every time.

With Perma “R” Products... We’ve Got You Covered.

*All roof underlayments may be slippery when wet or covered with mud, dust, frost, ice or snow. Always follow OSHA fall protection guidelines and use caution.



WHAT'S UNDER YOUR ROOF



PROFELT^{PLUS} PROFESSIONAL GRADE ROOF UNDERLAYMENT

- Replaces #15 asphalt felt
- 3.2 oz/yd²
- Meets and exceeds ASTM D226
- Non-woven fibrous laminated for better traction
- UV protected for 45 days
- 11 times stronger than #30 felt
- Does not promote mold growth
- Class A Fire
- Low temp flexibility
- Recyclable
- For use under asphalt and synthetic shingles
- Intertek CCRR-1116

PROFELT³⁰ PROFESSIONAL GRADE ROOF UNDERLAYMENT

- Replaces #30 asphalt felt
- 3.8 oz/yd²
- Meets and exceeds ASTM D226
- Non-woven fibrous laminated for better traction
- UV protected for 90 days
- 20 times stronger than #30 felt
- Does not promote mold growth
- Class A Fire
- Low temp flexibility
- Recyclable
- For use under metal, shake, and shingle roofing
- Intertek CCRR-1053

PERMAFELT^{SILVER} PROFESSIONAL GRADE ROOF UNDERLAYMENT

- Replaces asphalt felt
- 3.9 oz/yd²
- Meets and exceeds ASTM D226
- Proprietary rubberized coating for better traction
- UV protected for 180 days
- 15 times stronger than #30 felt
- Does not promote mold growth
- Class A Fire
- Low temp flexibility
- Recyclable
- For use under metal, shake, tile, slate, and shingle roofing
- Intertek CCRR-1053

PERMAFELT^{GOLD} PROFESSIONAL GRADE ROOF UNDERLAYMENT

- Replaces asphalt felt
- 4.3 oz/yd²
- Meets and exceeds ASTM D226
- Proprietary rubberized coating for better traction
- UV protected for 180 days
- 22 times stronger than #30 felt
- Does not promote mold growth
- Class A Fire
- Low temp flexibility
- Recyclable
- For use under premium metal, shake, tile, slate, and shingle roofing
- Intertek CCRR-1053

TECHNICAL DATA SHEET

Affix double sided tape here 6x3

PLUS
PROFELT
PROFESSIONAL GRADE ROOF UNDERLAYMENT

Product Specifications			Test Method
Basis Weight / Roll Weight	3.0oz/yd ² (+/-5%) / 2.3 lbs/square		
Tensile Strength	MD 106 LB	CD 108 LB	ASTM D5034
Tear Strength	MD 30 LB	CD 30 LB	ASTM D4533
Elongation	MD 18%	CD 15%	ASTM D5035
Water Transmission	PASS		ASTM D4869
Water Ponding	PASS		AC48 Sec. 4.4
UV Weathering	45 days		
Class A Fire Resistance	ASTM E108		

Affix double sided tape here

30
PROFELT
PROFESSIONAL GRADE ROOF UNDERLAYMENT

Product Specifications			Test Method
Basis Weight / Roll Weight	3.8oz/yd ² (+/-5%) / 2.3 lbs/square		
Tensile Strength	MD 100 LB	CD 80 LB	ASTM D5034
Tear Strength	MD 42 LB	CD 40 LB	ASTM D4533
Elongation	MD 17%	CD 18%	ASTM D751
Water Transmission	PASS		ASTM D4869
Water Ponding	PASS		AC48 Sec. 4.4
UV Weathering	90 days		
Class A Fire Resistance	ASTM E108, UL 790, UBC 15-2		

Affix double sided tape here

SILVER
PERMAFELT
PROFESSIONAL GRADE ROOF UNDERLAYMENT

Product Specifications			Test Method
Basis Weight / Roll Weight	3.9oz/yd ² (+/-5%) / 2.8 lbs/square		
Tensile Strength	MD 94 LB	CD 93 LB	ASTM D5034
Tear Strength	MD 33 LB	CD 30 LB	ASTM D4533
Pliability	PASS		AC48 Sec. 4.3
Water Transmission	PASS		ASTM D4869
Water Ponding	PASS		AC48 Sec. 4.4
UV Weathering	180 days		
Class A Fire Resistance	ASTM E108, UL 790, UBC 15-2		

Affix double sided tape here

GOLD
PERMAFELT
PROFESSIONAL GRADE ROOF UNDERLAYMENT

Product Specifications			Test Method
Base Weight / Roll Weight	4.3oz/yd ² (+/-5%) / 3lb per square		
Tensile Strength	MD 120 LB	CD 112 LB	ASTM D5034
Tear Strength	MD 52 LB	CD 43 LB	ASTM D4533
Fastener Seal Ability	PASS		ASTM D1970-1
Water Transmission	PASS		ASTM D4869
Water Ponding	PASS		AC48 Sec. 4.4
UV Weathering	180 days		
Class A Fire Resistance	ASTM E108, UL 790, UBC 15-2		

2604 SUNSET DR. GRENADA, MS 38901

1-800-647-6130

WWW.PERMARPRODUCTS.COM

Updated 7 - 18

