

CONTRACTOR **PRO** GRADE SHEATHING TAPE

For building Wraps and a variety of construction materials

PERMA "R" PRODUCTS™ TECHNICAL DATA SHEET

Perma R Item #	Roll Dimension	Item UPC	Case Qty (rolls)	Case UPC	Pallet Qty (cases)
18755 (white)	48mm x 50m	02800618755 6	24	30028006187557	48

DESCRIPTION

Aggressive solvent based acrylic combined with flexible polypropylene film provides superior sealing and protective benefits. Designed for permanent seaming and sealing of joints in foam insulation and other sheathing materials, to secure lap edges in housewraps and other vapor barriers, repair rips and tears in roll and batt insulation, construction films and membranes. Eliminates drafts around window and door openings. Superior bonding at sub-zero (as low as -40°C/F) or at elevated temperatures.

COMMON APPLICATIONS

Multi-purpose construction tape to prevent air infiltration, provide vapor barrier protection, and enhance appearance. Surfaces to be clean/dry. Do not apply to wet surfaces (facing or wood). May be hand or machine applied. Lap intersecting or joined tapes a minimum 50.8mm (2"). Tape should be centered over the joint or other area to be sealed. Butt joints should not exceed 10mm (0.3937") in width.



PO Box 279 | Grenada, MS 38902 | USA

Customer Service: 800.647.6130

www.permarproducts.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

PHYSICAL PROPERTIES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	1.6 mil (40μ) BOPP
Tensile Strength (lbs/in of width) ASTM-D3759	32 (140N/25mm)
Elongation (% at break)	190
Adhesive	Solvent Cast Acrylic
90° Adhesion to Steel (oz/in of width) PSTC-101F	64.5 (17.6N/25mm)
180° Adhesion	20.3 (5.5N/25mm)
Quick Stick to Steel PSTC-5	31 (8.5N/25mm)
Total Thickness (mils) PSTC-33	3.4 (0.086mm)
Color	White

