

SHEATHING TAPE

WE'VE GOT YOU COVERED

Don't Forget the Tape!

Perma "R" Sheathing Tape, an aggressive solvent based acrylic tape designed for permanent seaming and sealing of joints in foam insulation and other sheathing materials. Now you can easily secure lap edges, repair rips and tears in roll when installing house wraps, construction films and membranes.



SHEATHING TAPE
CONTRACTOR PRO GRADE



Features & Benefits

- Contractor PRO grade, multi-purpose, flexible polypropylene sheathing tape
- Provides superior sealing where needed with construction air, water, and vapor materials
- Tearable by hand for easy installation
- Eliminates drafts around window & door openings
- Superior bonding at subzero (as low as -40°C/F) or elevated temperatures

| Perma R Item # | Roll Dimensions | Item UPC | Case QTY (rolls) | Case UPC | Pallet QTY (cases) |
|----------------|-----------------|---------------|------------------|----------------|--------------------|
| 18755 (white) | 48mm x 50m | 02800618755 6 | 24 | 30028006187557 | 48 |



| Properties | Specs | Test |
|--|----------------------|------------|
| Backing | 1.6 mil (40μ) BOPP | — |
| Tensile Strength (lbs/in of width) | 32 (140N/25mm) | ASTM-D3759 |
| Elongation (% at break) | 190 | — |
| Adhesive | Solvent Cast Acrylic | — |
| 90° Adhesion to Steel (oz/in of width) | 64.5 (17.6N/25mm) | PSTC-101F |
| 180° Adhesion | 20.3 (5.5N/25mm) | — |
| Quick Stick to Steel | 31 (8.5N/25mm) | PSTC-5 |
| Total Thickness (mils) | 3.4 (0.086mm) | PSTC-33 |
| Color | White | — |

The above data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Best Application Practices

- Make sure surfaces are clean and dry
- Do not apply to wet surfaces (facing or wood)
- May be hand or machine applied
- Lap intersecting or joined tapes a minimum 50.8mm (2")
- Tape should be centered over the joint or other area to be sealed
- Butt joints should not exceed 10mm (0.3937") in width

Perma "R" Building Products assumes no liability, expressed or implied, as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents. Contact Perma "R" Building Products for further information or technical support.

*Due to the variable surface of substrates such as OSB, concrete, CMU and fiberglass gypsum board adhesion should be tested prior to installation, as a primer may be required to ensure adequate adhesion.

Individual jurisdictions and principalities may vary. Check with your local building officials for approval and acceptance.



PERMA "R" PRODUCTS®
WE'VE GOT YOU COVERED

permarproducts.com | 800.647.6130



© 2024 Perma "R" Products, Inc.

PRP Sheathing Tape 3-24